

**IC-F510/F610** 25 Watt, 256 Channel Mobile Transceiver, comes in Wide/Narrow configurations including Built-In 5 Tone CTCSS & DTCS Encode/Decode, DTMF Encoder with ANI functions  
 Supplied with HM152 Hand Mic., Mounting Bracket kit

**IC-F510** VHF 148-174MHz, 12.5/25kHz Channel spacing  
**IC-F610F2** UHF 440-490MHz, 12.5/25kHz Channel spacing

**Voting Version**  
**IC-F510V** Voting VHF 136-174MHz, 12.5/25kHz Channel spacing  
**IC-F610F2V** Voting UHF 440-490MHz, 12.5/25kHz Channel spacing

#### **Microphones**

HM152 Microphone (Non Keypad)  
 HM152T DTMF Microphone  
 HM148 Heavy duty microphone (non keypad)  
 SM25 Desk Microphone, Monitor Switches

#### **Data Cables**

OPC-617 External Modem Connection Cable

#### **Voice Privacy Options**

UT109#02 Scrambler Frequency Inversion Type  
 UT110#02 Scrambler Rolling Code Type

#### **Signaling Options**

UT108 DTMF Decoder Unit  
 UT111 LTR Trunking Unit  
 100 Option Fitting Fee

#### **Installation Options**

OPC-346 DC Cable, 20A, 3m (same as supplied)

#### **External Speakers**

SP10 Miniature External Speaker  
 SP22 Standard External Speaker

#### **Programming Equipment**

CS-F510 Dealer Programming Software disc  
 OPC-1122 RS232 Programming Adaptor cable  
 OPC-1122U USB Programming Cable

#### **Power Base Kits**

SEC1212 DC Power Supply-for ground installation  
 SEC12120 Base Station Cabinet to suit IC-F510  
 DRC11357 Desktop Repeater Cabinet  
 RPT-F210 Repeater Interface Unit